

Asymptotics of the Quantum Hamming Bound for Subsystem Codes

Andreas Klappenecker and Pradeep Kiran Sarvepalli

Department of Computer Science, Texas A&M University, College Station, TX 77843, USA

(Dated: February 2, 2008)

Ashikhmin and Litsyn showed that all binary stabilizer codes – pure or impure – of sufficiently large length obey the quantum Hamming bound, ruling out the possibility that impure codes of large length can outperform pure codes with respect to sphere packing. In contrast we show that impure subsystem codes do not obey the quantum Hamming bound for pure subsystem codes, not even asymptotically. We show that there exist arbitrarily long Bacon-Shor codes that violate the quantum Hamming bound.

Keywords: quantum Hamming bound, asymptotic bounds, degenerate codes, subsystem codes

Degenerate quantum error-correcting codes pose many interesting questions in the theory of quantum error-correction. The early discovery of the phenomenon of degeneracy raised the question whether degenerate quantum codes can perform better than nondegenerate quantum codes. One of the unresolved questions to this day in the theory of stabilizer codes is whether the bounds that hold for nondegenerate codes also hold for degenerate codes. Some bounds like the quantum Singleton bound do. But for others, like quantum Hamming bound, an answer remains elusive. Partial answers were provided by Gottesman [5] for single error-correcting and double error-correcting codes. Ashikhmin and Litsyn [2] showed that asymptotically degenerate codes cannot beat the quantum Hamming bound. *This leaves only a small range of degenerate binary stabilizer codes of moderate length that can potentially beat the quantum Hamming bound, but we conjecture that no such examples can be found.*

We show that the situation is markedly different in the case of subsystem codes (also known as operator quantum error-correcting codes [7, 8, 9]). The quantum Hamming for pure subsystem codes was derived in [1]. In [6], it was shown that there exist impure subsystem codes that beat the quantum Hamming bound for pure subsystem codes. However, it remained unclear whether impure subsystem codes asymptotically obey the quantum Hamming bound, as in the case of binary stabilizer codes. The purpose of this note is to show that there exist impure subsystem codes of arbitrarily large length that beat the quantum Hamming (or sphere-packing) bound.

Recall that the quantum Hamming bound for subsystem codes states that a pure $[[n, k, r, d]]$ subsystem code satisfies

$$2^{n-k-r} \geq \sum_{j=0}^{\lfloor (d-1)/2 \rfloor} \binom{n}{j} 3^j. \quad (1)$$

For all positive integers n , there exist subsystem codes

with parameters $[[n^2, 1, (n-1)^2, n]]$ – the Bacon-Shor codes, see [3, 4]. We claim that all $[[(2t+1)^2, 1, 4t^2, 2t+1]]$ subsystem codes violate the quantum Hamming bound, namely that

$$2^{(2t+1)^2 - 1 - 4t^2} = 2^{4t} \not\geq \sum_{j=0}^t \binom{(2t+1)^2}{j} 3^j$$

holds for all positive integers t . It suffices to show that

$$2^{4t} < \binom{(2t+1)^2}{t} 3^t \quad (2)$$

holds for all positive integers t . Since $0 < 4(t-1/6)^2 + 8/9 = 4t^2 - 4t/3 + 1$, we have

$$\frac{16t}{3} < 4t^2 + 1 + 4t$$

for all $t > 0$. Multiplying both sides by $3/t$ and raising to the t^{th} power yields

$$2^{4t} < \frac{3^t (2t+1)^{2t}}{t^t},$$

which proves the inequality (2), as $\binom{n}{k} \geq n^t k^{-t}$. Thus, we can conclude that the Bacon-Shor codes of odd length do not obey the quantum Hamming bound.

Theorem 1 *Asymptotically, the quantum Hamming bound (1) does not hold for impure subsystem codes.*

It is remarkable that there exist such families of subsystem codes that can pack more densely than any pure subsystem code. Further examples of such densely packing subsystem codes can be found among the family with parameters $[[n_1 n_2, 1, (n_1-1)(n_2-1), \min\{n_1, n_2\}]]$, which contains for instance a $[[12, 1, 6, 3]]$ subsystem code.

[1] S. A. Aly, A. Klappenecker, and P. K. Sarvepalli. Subsystem codes. In *Forty-Fourth Annual Allerton Conference*

ence on Communication, Control, and Computing, Illi-

- nois, USA*, 2006. eprint:quant-ph/0610153.
- [2] A. Ashikhmin and S. Litsyn. Upper bounds on the size of quantum codes. *IEEE Trans. Inform. Theory*, 4:1206–1216, 1999.
 - [3] D. Bacon. Operator quantum error correcting subsystems for self-correcting quantum memories. *Phys. Rev. A*, 73(012340), 2006.
 - [4] D. Bacon and A. Casaccino. Quantum error correcting subsystem codes from two classical linear codes. In *Forty-Fourth Annual Allerton Conference on Communication, Control, and Computing, Illinois, USA*, 2006.
 - [5] D. Gottesman. Stabilizer codes and quantum error correction. Caltech Ph. D. Thesis, eprint: quant-ph/9705052, 1997.
 - [6] A. Klappenecker and P. K. Sarvepalli. On subsystem codes beating the quantum Hamming or Singleton bound. *Proc. Roy. Soc. A.*, 463:2887–2905, 2007.
 - [7] E. Knill. Protected realizations of quantum information. *Phys. Rev. A*, 74(042301), 2006.
 - [8] D. W. Kribs, R. Laflamme, and D. Poulin. A unified and generalized approach to quantum error correction. *Phys. Rev. Lett.*, 94(180501), 2005.
 - [9] D. W. Kribs, R. Laflamme, D. Poulin, and M. Lesosky. Operator quantum error correction. *Quantum Information & Computation*, 6:382–399, 2006.